

INTAKE SYSTEM OF INTERNAL COMBUSTION ENGINE

TECHNICAL FIELD

5 The present invention relates to an intake system of an internal combustion engine, and specifically to technologies for a collector equipped intake system of an internal combustion engine.

BACKGROUND ART

10 Collector equipped intake systems for an internal combustion engine are well known. On such collector equipped intake systems, it would be desirable to ensure simplicity in installation and to enhance the supporting rigidity, simplifying the construction of the intake system without reducing dynamic characteristics of air
15 drawn into the engine.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the invention to provide a compactly designed, collector equipped intake system of an internal combustion engine, which is capable
20 of enhancing design simplicity, simplicity in installation, and supporting rigidity without sacrificing dynamic characteristics of air drawn into the engine, and of reducing noise and vibration input to the collector.

25 It is another object of the invention to provide a compactly designed, collector equipped intake system with variable valve actuation system interaction, which is capable of realizing both the shortened axial length of each of intake-manifold branches and enlarged capacity
30 of the collector.

It is a further object of the invention to provide a compactly designed, collector equipped intake system with vacuum control valve interaction, which is capable

of enhancing combustion stability during low load operation such as idling and of enhancing charging efficiency during high load operation.

In order to accomplish the aforementioned and other
5 objects of the present invention, an intake system of an internal combustion engine comprises a collector fixedly connected directly to either of a side wall of a cylinder head and a collector mounting bracket
10 hermetically covering perimeters of intake-port opening end portions of a plurality of intake ports opening through the side wall, and a plurality of intake-manifold branches respectively communicating with the plurality of intake ports and protruded into an interior space of the collector.

15 The other objects and features of this invention will become understood from the following description with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a cross-sectional view illustrating a first
20 embodiment of an intake system.

Fig. 2 is a cross-sectional view taken along the line II-II of Fig. 1.

Fig. 3 is an explanatory view illustrating a state of installation of a collector on a collector mounting
25 bracket.

Fig. 4 is an enlarged cross sectional view showing the connecting portion between two-split collector component parts.

Fig. 5 is a perspective view illustrating a variable
30 valve actuation system.

Fig. 6 is a chart illustrating valve lift characteristics under exemplary operating conditions of the engine.

Figs. 7A-7F are timing charts showing the relationship among a collector vacuum, a vacuum control valve opening, a working angle EA of an intake valve, a phase of a central angle ϕ of the working angle of the intake valve, intake valve closure timing IVC, and intake valve open timing IVO.

Fig. 8 is a comparative diagram showing a collector vacuum versus engine torque characteristic obtained by throttle valve control and a collector vacuum versus engine torque characteristic obtained by variable lift and working angle control plus vacuum control valve control.

Fig. 9 shows pressure/volume diagrams (P-V diagrams) used to comparison between a pumping loss obtained by a throttle-less intake system and a pumping loss obtained by a throttle-equipped intake system.

Fig. 10 is a cross-sectional view illustrating a second embodiment of an intake system.

Fig. 11 is a cross-sectional view taken along the line XI-XI of Fig. 10.

Fig. 12 is a cross-sectional view illustrating a third embodiment of an intake system.

Fig. 13 is a cross-sectional view illustrating the layout of intake-air inlets of the intake system of the third embodiment.

Figs. 14A-14C are 1st valve timing characteristics, respectively showing idling, a middle load condition, and a high load condition.

Figs. 15A-15C are 2nd valve timing characteristics, respectively showing idling, a middle load condition, and a high load condition.

Figs. 16A-16C are 3rd valve timing characteristics, respectively showing idling, a middle load condition, and a high load condition.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

5 Referring now to the drawings, particularly to Figs. 1-4, the intake system of the embodiment is exemplified in a four-cycle gasoline engine. The internal combustion engine having the intake system of the embodiment is further equipped with a variable valve actuation system
10 shown in Fig. 5. The variable valve actuation system of Fig. 5 is combined with an intake system of the second embodiment (described later in reference to Figs. 10 and 11) and an intake system of the third embodiment (described later in reference to Figs. 12 and 13), in addition to
15 the intake system of the first embodiment of Figs. 1-4. The variable valve actuation system serves to variably adjust a valve lift characteristic (a valve timing and a valve lift) of an intake valve 1. The variable valve actuation system is comprised of a variable lift and
20 working angle control mechanism (or a variable valve event and lift mechanism) 10 and a variable phase control mechanism 20. Variable lift and working angle control mechanism 10 serves to continuously variably adjust the working angle and lift of intake valve 1. Variable phase
25 control mechanism 20 serves to continuously variably adjust a phase of a central angle of the working angle of intake valve 1 (the angular phase at the maximum valve lift point of intake valve 1) with respect to an engine crankshaft (not shown). Variable lift and working angle
30 control mechanism 10 includes a drive shaft 11 and a control shaft 12 both extending in the cylinder row direction and arranged parallel to each other. Drive shaft 11 is rotated about its axis by torque transmitted from the

crankshaft to the drive shaft. Rockable cam 13 is oscillatingly fitted onto the outer periphery of drive shaft 11. Rockable cam 13 is in abutted-engagement with a valve lifter or a tappet 2 attached to the upper portion of the valve stem of intake valve 1. Eccentric cam 14 is fixedly connected or integrally formed with drive shaft 11 for each engine cylinder. The axis of the outer peripheral surface of eccentric cam 14 is eccentric to the axis of drive shaft 11. A substantially ring-shaped first link 15 is rotatably fitted onto the outer periphery of eccentric cam 14. A control cam 16 is fixedly connected to or integrally formed with control shaft 12 for each engine cylinder. The axis of the outer peripheral surface of control cam 16 is eccentric to the axis of control shaft 12. A substantially cylindrical hollow central portion of a rocker arm 17 is rotatably fitted onto the outer periphery of control cam 16. Rocker arm 17 is connected at one end to the extruded portion of first link 15 in a manner so as to permit relative rotation of rocker arm 17 to first link 15. Rocker arm 17 is connected at the other end to one end of a rod-shaped second link 18 in a manner so as to permit relative rotation of rocker arm to second link 18. The other end of second link 18 is connected to the extruded portion of rockable cam 13 in a manner so as to permit relative rotation of second link 18 to rockable cam 13. With the previously noted arrangement, when drive shaft 11 rotates in synchronism with rotation of the crankshaft, a translation motion of first link 15 fitted onto eccentric cam 14 takes place. The translation motion of first link 15 is converted into an oscillating motion of rocker arm 17. The oscillating motion of rocker arm 17 is transmitted via second link 18 to rockable cam 13, thereby causing

an oscillating motion of rockable cam 13. Rockable cam 13 is formed on its lower surface with a base-circle surface portion being concentric to drive shaft 11 and a moderately-curved cam surface portion being continuous with the base-circle surface portion and extending toward one end portion of rockable cam 13. The base-circle surface portion and the cam surface portion of rockable cam 13 are designed to be brought into abutted-contact (sliding-contact) with a designated point or a designated position of the upper surface of the associated intake-valve lifter 2, depending on an angular position of rockable cam 13 oscillating. That is, the base-circle surface portion functions as a base-circle section within which a valve lift is zero. A predetermined angular range of the cam surface portion being continuous with the base-circle surface portion functions as a ramp section. A predetermined angular range of a cam nose portion of the cam surface portion being continuous with the ramp section functions as a lift section. By virtue of cam action of rockable cam 13 oscillating, intake-valve lifter 2 is pushed and therefore intake valve 11 lifts. When control shaft 12 is driven within a predetermined angular range by means of a variable lift and working angle control actuator 19, the center of control cam 16 serving as a center of oscillating motion of rocker arm 17 varies. Owing to the change in the center of oscillating motion of rocker arm 17, attitudes of rocker arm 17, first link 15, and second link 18 vary. Therefore, a characteristic of oscillating motion of rockable cam 13 varies. As a consequence, both of the working angle and valve lift of intake valve 1 can be continuously adjusted.

In the previously discussed variable lift and working angle control mechanism 10, rockable cam 13, capable of

opening and closing intake valve 1, is coaxially arranged on drive shaft 11. Thus, there is no possibility of an undesirable offset between the axis of rockable cam 13 and the axis of drive shaft 11. Such coaxial arrangement is superior in control accuracy. Variable lift and working angle control mechanism 10 is compactly designed, since rocker arm 17, first and second links 15 and 18 are concentrated around drive shaft 11. That is, the compactly designed variable lift and working angle control mechanism 10 is superior in simplicity in installation (time saved in installation). In the bearing portion between eccentric cam 14 and first link 15, there is wall contact between the outer peripheral wall surface of eccentric cam 14 and the inner peripheral wall surface of first link 15. In a similar manner, in the bearing portion between control cam 16 and rocker arm 17, there is wall contact between the outer peripheral wall surface of control cam 16 and the inner peripheral wall surface of rocker arm 17. In comparison with spot contact or line contact, the wall contact is superior in enhanced lubricating performance, and enhanced durability and reliability of moving parts. Variable lift and working angle control mechanism 10 is easily applicable to a conventional non-variable valve actuation system with a cam fixedly connected to a camshaft. That is, rockable cam 13 may be easily laid out within an installation space of the cam fixed to the camshaft, while the camshaft may be easily replaced with drive shaft 11. In other words, the compactly designed variable lift and working angle control mechanism 10 facilitates the design change from the conventional non-variable valve actuation system.

Variable phase control mechanism 20 is provided to continuously change the phase of the central angle of

the working angle of intake valve 1 by changing the phase of drive shaft 11 relative to the crankshaft. A vane-type phase control mechanism or a helical-spline type phase control mechanism is widely used as the variable phase control mechanism. Variable phase control mechanism 20 is comprised of a sprocket (not numbered) and a phase control actuator (not numbered). The sprocket is provided at the front end of drive shaft 11 and has a driven connection with the engine crankshaft through a timing chain (not shown) or a timing belt (not shown). The phase control actuator is provided to enable drive shaft 11 to rotate relative to the sprocket within a predetermined angular range. The previously noted variable lift and working angle control actuator 19 and the phase control actuator are controlled in response to control signals from an electronic control unit (ECU) 4 which will be fully described later. Relative rotation of drive shaft 11 to the sprocket in one rotational direction results in a phase advance at the maximum intake-valve lift point (at the central angle of the working angle of intake valve 1). Relative rotation of drive shaft 11 to the sprocket in the opposite rotational direction results in a phase retard at the maximum intake-valve lift point. That is, only the phase of working angle (i.e., the angular phase at the central angle) is advanced or retarded, with no valve-lift change and no working-angle change. The relative angular position of drive shaft 11 to the sprocket can be continuously varied within limits by means of the phase control actuator, and thus the angular phase at the central angle also vary continuously.

ECU 4 generally comprises a microcomputer. ECU 4 includes an input/output interface (I/O), memories (RAM,

ROM), and a microprocessor or a central processing unit (CPU). The input/output interface (I/O) of ECU 4 receives input information from various engine/vehicle sensors, namely engine speed, engine load, engine temperature and the like. Within ECU 4, the central processing unit (CPU) allows the access by the I/O interface of input informational data signals from the previously discussed engine/vehicle sensors. The CPU of ECU 4 is responsible for carrying the variable valve lift characteristic control (working angle and lift control/variable phase control) program as well as fuel-injection control program stored in memories and is capable of performing necessary arithmetic and logic operations based on operating conditions of the engine. Computational results (arithmetic calculation results), that is, calculated output signals (actuator drive currents) are relayed via the output interface circuitry of ECU 4 to output stages, namely electromagnetic fuel-injection valves, the variable phase control actuator and variable lift and working angle control actuator 19. The quantity of air drawn into the engine can be adjusted by changing the lift characteristic of intake valve 1. For instance, the intake-air quantity can be reduced by advancing the intake valve closure timing IVC from bottom dead center (BDC). It is possible to decrease the intake-air quantity by decreasingly compensating for both the working angle and valve lift of intake valve 1. The variable valve lift characteristic control for intake valve 1 eliminates the necessity of a throttle valve that is generally used to admit more or less intake air. In other words, it is possible to realize a throttle-less construction in the intake system.

Referring now to Fig. 6, there is shown the intake-valve lift characteristics under exemplary five different engine operating conditions, namely at idle, at part load whose condition is often abbreviated to "R/L (Road/load)" substantially corresponding to a 1/4 throttle opening, during moderate acceleration, at full load and low speed, and at full load and high speed. As shown in Fig. 6, at the idling condition ① and at the part load condition ②, in order to reduce a pumping loss, the working angle of intake valve 1 is controlled to a comparatively small value, the central angle of the working angle of intake valve 1 is phase-advanced so that the intake valve open timing IVO is set nearby top dead center (TDC), and the intake valve closure timing IVC is phase-advanced to a considerably earlier point before bottom dead center (BBDC), thereby reducing the actual intake stroke.

Under the moderate acceleration condition ③, the working angle is somewhat enlarged in comparison with that of the idling condition ① or the part load condition ② and controlled to a substantially middle working angle. The phase of the central angle under moderate acceleration condition ③ is somewhat advanced, but phase-retarded as compared to the idling condition ① and part load condition ②.

Under the full load and low speed condition ④, the working angle of intake valve 1 is further increased as compared to moderate acceleration condition ③, and controlled to a low-speed full-load working angle suitable for low engine speed. Additionally, the phase of the central angle is controlled to a standard central angle retarded with respect to the central angle under moderate acceleration condition ③. Under the full load and low

speed condition ④, the intake valve open timing IVO is adjusted to a timing point just before top dead center (BTDC), and additionally the intake valve closure timing IVC is adjusted to a timing point just after bottom dead center (ABDC), thereby enhancing the charging efficiency of intake air.

Under the full load and high speed condition ⑤, the working angle is further enlarged and additionally the phase of the central angle is further retarded in comparison with the full load and low speed condition ④. As a consequence, the intake valve closure timing IVC is further retarded to a timing point after BDC.

As previously described, by virtue of the variable intake valve lift characteristic control, it is possible to provide the throttle-less construction in the intake system. The throttle-less construction is effective to reduce the pumping loss under low and middle load conditions. Referring to Fig. 9, there is shown the two different P-V diagrams respectively indicated by the solid line and the broken line. The P-V diagram indicated by the solid line is a diagram of a four-stroke cycle at part load operation and obtained by the throttle-less intake system with variable valve actuation system interaction. In contrast, the P-V diagram indicated by the broken line is a diagram of a four-stroke cycle at the same part load operation and obtained by the throttle equipped intake system. As can be appreciated from comparison between the two different P-V diagrams of Fig. 9, it is possible to greatly reduce the pumping loss by using the throttle-less intake system with variable valve actuation system interaction.

Returning to Figs. 1-4, in the intake system of the first embodiment, a collector mounting bracket 36 is

fixedly connected to an intake-port side wall 32 of a cylinder head 30, so that collector mounting bracket 36 hermetically covers the perimeters of intake-port opening end portions (35, 35, 35, 35) of a plurality of intake
5 ports (34, 34, 34, 34). Intake ports 34 of a plurality of engine cylinders constructing a cylinder row are located on side wall 32. In the shown embodiment, the number of the cylinders is four. In the intake system of the first embodiment, note that one collector 38 is
10 fixedly connected directly to collector mounting bracket 36. A plurality of intake-manifold branches (40, 40, 40, 40) are protruded into the interior space of collector 38. Intake-manifold branches (40, 40, 40, 40) communicate the respective intake ports (34, 34, 34, 34).
15 As can be appreciated from the cross sections shown in Figs. 1, 2, and 4, collector 38 has a two-split structure. Actually, collector 38 is split into two parts, namely an upper collector portion 42 and a lower collector portion 44, both made of a lightweight synthetic resin material.
20 An air cleaner 46 is located in collector 38, so that air cleaner 46 is interleaved between two-split upper and lower collector portions 42 and 44. As best seen from the enlarged cross section of Fig. 4, upper and lower collector portions 42 and 44 are detachably connected
25 to each other by means of a clip 50, so that air cleaner 46 and a gasket 48 are sandwiched between upper and lower collector portions 42 and 44 in an air-tight fashion. Each of upper and lower collector portions 42 and 44 is partially formed with a recessed portion 52, which is
30 brought into engagement with the clip when assembling upper and lower collector portions 42 and 44. The two-dotted line H of Fig. 4 shows a cross section of each of upper and lower collector portions 42 and 44, except

for recessed portions 52 engaged with clip 50. As shown in Fig. 3, lower collector portion 44 constructing a major part of collector 38 has upper-flanged portions (55, 55) and lower-flanged portions (57, 57). Upper-flanged portions (55, 55) are fixedly connected to collector mounting bracket 36 by means of bolts (54, 54). Similarly, lower-flanged portions (57, 57) are fixedly connected to cylinder head 30 or to cylinder block 31 by means of bolts (56, 56) or to a mounting bracket fixedly connected to either of the cylinder head and the cylinder block.

Referring to Fig. 2, upper collector portion 42 is integrally formed with a substantially cylindrical intake-air inlet 58. An intake pipe 62 is connected to intake-air inlet 58, placing a gasket 60 between an inner peripheral surface of intake-air inlet 58 and an outer peripheral surface of intake pipe 62 to provide a tight seal between them. A pressure control valve (exactly, a vacuum control valve) 64 is disposed in intake pipe 62 upstream of the collector. Vacuum control valve 64 is provided to create a minimum vacuum needed for the engine (a vacuum-operated blow-by gas recirculation system, an evaporative emission control system employing a vacuum-operated purge valve, and the like), rather than adjusting the intake-air quantity. Vacuum control valve 64 is controlled in response to a control command from ECU 4, depending on engine operating conditions, such as engine speed and engine load (an accelerator opening or a throttle opening). A filter 66 having a lower filtering function (larger meshes) than air cleaner 46 is installed on the opening end of intake pipe 62, so as to remove dust, dirt, and other contaminants and to prevent a mechanical problem such as a sticking vacuum

control valve which may occur owing to entry of dust, dirt, and other contaminants into intake pipe 62.

Returning to Fig. 1, as can be appreciated from the cross section of collector 38 cut by the vertical plane, lower collector portion 44 constructing a major part of collector 38 has a plurality of first branch portions (68, 68, 68, 68), a recessed portion 72, and a mounting plate portion 74, integrally formed with each other. Each of first branch portions 68 is substantially cylindrical in shape and protruded into the interior space of collector 38 (in particular, lower collector portion 44). Each of the first branch portions constructs a part of the associated intake-manifold branch 40. Recessed portion 72 is provided to avoid the interference between collector 38 and a fuel injection valve 70 that injects fuel spray into intake port 34. Mounting plate portion 74 is fixedly connected to collector mounting bracket 36 in such a manner as to be kept in wall contact with the flat surface portion of collector mounting bracket 36. Mounting plate portion 74 is relatively thick-walled in comparison with the other collector portions, to increase rigidity in installation.

In the same manner as cylinder head 30, collector mounting bracket 36 is made of aluminum alloy having a high rigidity. Collector mounting bracket 36 has a plurality of substantially cylindrical second branch portions (76, 76, 76, 76), an injector mounting boss portion 78, and a mounting plate portion 80, integrally formed with each other. Each of second branch portions 76 constructs the rest of the associated intake-manifold branch 40. Fuel injection valve 70 is mounted on or screwed into injector mounting boss portion 78. Mounting plate portion 80 is interleaved between side wall 32 of cylinder head 30 and mounting plate portion 74 of lower collector

portion 44. As shown in Fig. 3, collector mounting bracket 36 is fixedly connected to side wall 32 of cylinder head 30 by way of fastening means such as a plurality of bolts 82. Returning again to Fig. 1, the previously-noted
5 intake-manifold branch 40 means a substantially tubular portion defining a branch passage extending from intake-port opening end portion 35 of intake port 34 to a bell mouth shaped branch opening end portion 84 opening into the interior space of collector 38. In the intake
10 system of the first embodiment, intake-manifold branch 40 is constructed by first branch portion 68 and second branch portion 76, connected to each other, placing a gasket 86 between an inner peripheral surface of first branch portion 68 and an outer peripheral surface of second
15 branch portion 76 to provide a tight seal between them.

As will be appreciated from the above, in the intake system of the first embodiment, collector 38 is fixedly connected directly to collector mounting bracket 36 mounted on side wall 32 of cylinder head 30, thus enhancing
20 the rigidity needed to supporting the collector and reducing noise and vibration input to the collector. Collector 38 is located in close proximity to side wall 32 of cylinder head 30, and additionally almost all of each of intake-manifold branches 40 is built in collector
25 38. As a whole, the intake system can be compactly designed. Also, the intake system of the first embodiment is superior in ease of assembly and ease of installation. To realize the compact design (the layout) of the intake system as shown in Figs. 1-4, it is required to shorten the axial
30 length of intake-manifold branch 40 and to enlarge the capacity of collector 38. Two requirements, namely the shortened axial length of each of intake-manifold branches 40 and the enlarged capacity of collector 38 are satisfied

or realized by means of the previously-discussed variable valve actuation system (see Fig. 5), capable of adjusting the intake-air quantity by changing the valve lift characteristic of intake valve 1. As viewed from the lateral cross section shown in Fig. 1, a vertical dimension of collector 38, measured in the vertical direction of the engine substantially along the side wall 32 of cylinder head 30 is dimensioned to be longer than a horizontal dimension of collector 38, measured in the horizontal direction (in a cross direction of the engine), exactly in a direction substantially perpendicular to the side wall 32 of cylinder head 30. A dimension of collector 38 overhanging from the side wall of cylinder head 30 in the cross direction of the engine is reduced or suppressed. Additionally, it is possible to effectively use a dead space below the cylinder head. Thus, it is possible to more greatly enhance the supporting rigidity for collector 38 and simplicity in installation.

Furthermore, air cleaner 46 is interleaved between upper and lower halves 42 and 44 detachably connected to each other. Lower collector portion 44 is formed with first branch portions (68, 68, 68, 68) each constructing a part of the associated intake-manifold branch 40. As clearly shown in Fig. 1, air cleaner 46 is located above the bell mouth shaped branch opening end portion 84 of each of intake-manifold branches 40. Therefore, it is possible to easily replace the air cleaner with a new part only by removing upper collector portion 42 from lower collector portion 44 without removing upper collector portion 44 (providing most of the volumetric capacity of the collector) from the engine. Assuming that a valve overlap period during which both the intake and exhaust valves are open together is set to improve fuel

economy and to enhance engine power output, there is a tendency for high-temperature burned gases to flow back to the inlet port side. If air cleaner 46 is directly exposed to high-temperature burnt gases flowing backward, there is a possibility that the high-temperature burnt gases causes damage to or degradation in the air cleaner. For the reasons set out above, in the intake system of the shown embodiment, air cleaner 46 is laid out to be offset from a direction that each of intake-manifold branches 40 is protruded, that is, a discharge direction of burnt gases flowing backward. Concretely, a filtering surface of air cleaner 46 faces in a direction substantially normal to the direction that each of intake-manifold branches 40 is protruded, and air cleaner 46 is positioned or located above the protruded end of each of intake-manifold branches 40.

As clearly shown in Figs. 1 and 2, the intake system of the first embodiment also includes a blow-by gas recirculation system. The blow-by gas recirculation system is mainly comprised of a blow-by gas passage 98, which is connected at one end to a crankcase 31c of cylinder block 31 and at the other end to each of the branch passages (or intake-manifold branches 40) through lower collector portion 44. That is, "blow-by" gases escaping past a piston and piston rings into the crankcase, can be recirculated into the downstream side of vacuum control valve 64. One end of a fresh-air induction passage 99 is connected to the upper space of cylinder head 30, hermetically covered by a cylinder head cover 30h. The other end of fresh-air induction passage 99 is connected to intake pipe 62 upstream of vacuum control valve 64 (see Fig. 2). Additionally, the upper space defined in cylinder head 30 is communicated with crankcase 31c via

a communication passage (not shown). The basic operation of the blow-by gas recirculation system shown in Figs. 1 and 2 is similar to that of a conventional blow-by gas recirculation system of gasoline engines. That is,

5 "blow-by" gases escaping past the piston and piston rings into the crankcase, flows into each of the branch passages or intake-manifold branches 40 by virtue of a vacuum (a negative pressure) created in collector 38. At the same time, fresh air is introduced in the upper space of cylinder

10 head 30 via fresh-air induction passage 99. As fully described later, during full load operation that vacuum control valve 64 is operated at its full-open operating mode, part of the blow-by gas flows via fresh-air induction passage 99 back to intake pipe 62, and then flows into

15 the combustion chamber. Referring to Fig. 2, vacuum control valve 64 is comprised of a butterfly valve 92, a diaphragm type vacuum-operated actuator 94, and a two-position, three-port electromagnetic valve 95. Butterfly-shaped valve 92 is fixed to a rotation shaft

20 91 in such a manner as to open and close the fluid-flow passage of intake pipe 62. Vacuum-operated actuator 94 is mechanically linked via a linkage 93 to butterfly valve 92. A vacuum detection port 96 is formed in intake pipe 62 downstream of butterfly valve 92. Electromagnetic

25 valve 95 switches a vacuum to be fed to a vacuum chamber of vacuum-operated actuator 94 between the vacuum extracted by vacuum detection port 96 and the vacuum stored in a vacuum tank 97. That is, electromagnetic valve 95 serves to supply a selected one from the vacuum extracted

30 via the vacuum detection port and the vacuum in the vacuum tank to vacuum-operated actuator 94. Vacuum tank 97 is provided to store the vacuum, which is created by means of a vacuum pump (not shown) usually installed on the

vehicle for creating vacuum pressure needed for a brake booster or a diaphragm power brake included in a brake system. The vacuum stored in vacuum tank 97 is stronger or higher than the vacuum to be created in the collector.

5 During a normal engine operating condition, electromagnetic valve 95 is switched to establish fluid communication between vacuum detection port 96 and the vacuum chamber of vacuum-operated actuator 94. Thus, a comparatively weak vacuum created in collector 38 is
10 introduced into the vacuum chamber of vacuum-operated actuator 94, and as a result butterfly valve 92 opens. In the system of the embodiment, the weaker the vacuum introduced into the vacuum chamber of vacuum-operated actuator 94, the smaller the opening degree of butterfly
15 valve 92. Conversely, the stronger the vacuum introduced into the vacuum chamber of vacuum-operated actuator 94, the larger the opening degree of butterfly valve 92. Note that a strong or high vacuum caused by a closed vacuum control valve is indicative of a low pressure and vice
20 versa. Vacuum control valve 64 is responsive to the vacuum in collector 38 so that the vacuum pressure in collector 38 is brought closer to a desired vacuum pressure value (or a predetermined constant vacuum pressure value). That is, vacuum control valve 64 functions as a mechanical
25 collector-vacuum feedback control mechanism that the opening of butterfly valve 92 is automatically controlled or adjusted so that the vacuum pressure in collector 38 is brought closer to the desired vacuum pressure value. The desired vacuum pressure value is properly set, taking
30 into account characteristics of the blow-by gas recirculation system. For instance, the desired vacuum pressure value is set within a vacuum pressure range from -100 mmHg to -200 mmHg.

During a predetermined high load condition (containing a full load condition), electromagnetic valve 95 is switched to establish fluid communication between vacuum tank 97 and the vacuum chamber of vacuum-operated actuator 94. A comparatively strong vacuum stored in vacuum tank 97 is introduced into the vacuum chamber of vacuum-operated actuator 94. Thus, the opening degree of butterfly valve 92 of vacuum control valve 64 rapidly increases and the butterfly valve 92 is kept at its full-open position. As a consequence, a resistance of butterfly valve 92 to fluid flow is reduced to a minimum.

Referring now to Figs. 7A-7F, there are shown details of the operation of the variable valve actuation system of Fig. 5 and the operation of vacuum control valve 64 OF Fig. 2 in accordance with a change in engine load. As shown in Fig. 7C, the working angle EA of intake valve 1 increases, as the engine load increases. On the other hand, the phase of central angle ϕ of the working angle of intake valve 1 retards as the engine load increases (see Fig. 7D). The opening of vacuum control valve 64 tends to increase in accordance with an increase in the intake-air quantity, since the vacuum control valve opening is automatically controlled or adjusted so as to maintain the predetermined constant vacuum pressure. In the full load range, the vacuum control valve is forcibly held at the full-open position. As shown in Figs. 7E and 7F, as the engine load increases, intake valve open timing IVO is gradually advanced to a timing point before TDC, while intake valve closure timing IVC is retarded. The system of the embodiment employing vacuum control valve 64, exhibits a collector vacuum characteristic shown in Figs. 7A and 8, when increasing the engine load. As can be seen from the collector vacuum characteristic of Figs.

7A and 8, the vacuum in collector 38 is basically kept at the predetermined constant vacuum pressure value irrespective of the magnitude of engine load (or engine torque). The vacuum pressure in collector 38 becomes
5 almost zero (a less vacuum) only in the full-load range. In contrast to the above, in case of the usual throttle valve control using a conventional throttle valve, as indicated by the comparatively thin line in Fig. 8, the collector vacuum tends to decrease as the engine load
10 (engine torque) increases. The value of vacuum pressure caused by the closed vacuum control valve and the predetermined value of engine load above which vacuum control valve 64 is forcibly controlled to the full-open position are predetermined or preset, so that the value
15 of vacuum pressure mechanically feedback-controlled by means of vacuum control valve never exceeds the value of vacuum pressure created by the throttle valve.

Referring now to Figs. 10 and 11, there is shown the intake system of the second embodiment. As
20 appreciated from comparison between the cross section of the system of the first embodiment shown in Fig. 1 and the cross section of the system of the second embodiment shown in Fig. 10, the split position of upper and lower collector portions 42A and 44A of collector 38A of the
25 second embodiment is different from that of the first embodiment. In the second embodiment, of these two split collector portions 42A and 44A, upper collector portion 42A is larger than lower collector portion 44A and constructs a major part of collector 38A. Upper collector
30 portion 42A constructing the major part of collector 38A has a plurality of first branch portions (68A, 68A, 68A, 68A), a recessed portion 72A, and a mounting plate portion 74A, integrally formed with each other. Each of first

branch portions 68A is substantially cylindrical in shape and protruded into the interior space of upper collector portion 42A. Each of the first branch portions constructs a part of the associated intake-manifold branch 40.

5 Recessed portion 72A is provided to avoid the interference between collector 38A and fuel injection valve 70.

Mounting plate portion 74A is fixedly connected to collector mounting bracket 36 in such a manner as to be kept in wall contact with the flat surface portion of
10 collector mounting bracket 36. Mounting plate portion 74A is relatively thick-walled in comparison with the other collector portions, to increase rigidity in installation. As shown in Fig. 11, lower collector portion 44A is integrally formed with a substantially
15 cylindrical intake-air inlet 58A to which intake pipe 62 is connected, placing gasket 60 between the inner peripheral surface of intake-air inlet 58A and the outer peripheral surface of intake pipe 62 to provide a tight seal between them. As seen from the cross section of Fig.
20 11, a bottom surface of lower collector portion 44A integrally formed with intake-air inlet 58A, that is, a bottom surface 75 of collector 38A, is somewhat downwardly inclined toward intake-air inlet 58A under a specified condition that the collector equipped intake
25 system of the second embodiment is installed on the engine cylinder. Exactly speaking, bottom surface 75 of collector 38A is inclined by a predetermined inclination angle α with respect to a reference horizontal plane G, so that the bottom surface 75 of lower collector portion
30 44A gradually lowers toward intake-air inlet 58A. In presence of entrance of water or moisture into collector 38A due to snow and rain, the moisture or water can be rapidly exhausted to the exterior, while flowing along

the inclined bottom surface 75 of lower collector portion 44A. The inclined bottom surface 75 is effective to prevent water or moisture from being collected in the collector. In the system of the second embodiment shown in Figs. 10 and 11, a filtering surface of air cleaner 46 faces in a direction substantially normal to the direction that each of intake-manifold branches 40 is protruded, and air cleaner 46 is located below the protruded end of each of intake-manifold branches 40. Even when high-temperature burnt gases is discharged from the combustion chamber via each of intake-manifold branches 40 into collector 38A, there is a less possibility that air cleaner 46 is directly exposed to the burnt gases flowing backward. Thus, it is possible to prevent or avoid damage to or degradation in air cleaner 46 owing to the burnt gases.

Referring now to Figs. 12 and 13, there is shown the intake system of the third embodiment. Generally, there is an increased tendency for noise to be created near an intake-air inlet 58B integrally formed with a collector 38B (and near an intake pipe 62B) due to pulsations generated by each of engine cylinders. From the viewpoint of reduced noise and vibration, it is desirable to equally tune or adjust intervals of peak points of pulsations among a plurality of engine cylinders. Assuming that an effective distance or effective length from the inlet-valve port of intake valve 1 constructing part of the combustion chamber of each engine cylinder to intake-air inlet 58B is defined as an entire length of an intake-air passage containing the branch passage, it is desirable to provide as equal an entire intake-air passage length as possible for each engine cylinder. To realize this, in the intake system of the third embodiment

of Figs. 12 and 13, an upper collector portion 42B of collector 38B is formed integral with an auxiliary tube 90. As best seen in Fig. 13, auxiliary tube 90 is located at a substantially central portion of bell mouth shaped branch opening end portions 84B of the plurality of intake-manifold branches 40 in the cylinder row direction. Auxiliary tube 90 extends from the upper portion of upper collector portion 42B such that the opening end portion of auxiliary tube 90 curvedly extends towards cylinder head 31h. The opening end portion of auxiliary tube 90 constructs the intake-air inlet 58B. That is, as clearly shown in Fig. 13, intake-air inlet 58B and intake pipe 62B through which intake air is introduced into collector 38B are substantially centrally located in the cylinder row direction with respect to intake-manifold branches 40B of the plurality of engine cylinders (exactly, the plurality of bell mouth shaped branch opening end portions 84B). Additionally, bell mouth shaped branch opening end portions 84B are aligned with each other and substantially equidistantly spaced from each other in the cylinder row direction. As a consequence, the previously-noted entire intake-air passage length for each cylinder is almost the same. This is advantageous with respect to reduction in noise and vibration. In the intake system of the third embodiment having a shorter intake-manifold branch 40B and a larger capacity collector 38B than a conventional intake system, collector 38B has a major part of the entire intake-air passage length extending from the inlet-valve port of intake valve 1 to intake-air inlet 58B through which air is introduced into collector 38B. Therefore, in such an intake system having a shorter intake-manifold branch and a larger capacity collector, from the viewpoint reduced noise and vibration, it is very effective to

substantially centrally locate intake-air inlet 58B with respect to the plurality of bell mouth shaped branch opening end portions 84B of intake-manifold branches 40B in the cylinder row direction.

5 In the first (see Figs. 1-3), second (see Figs. 10-11), and third (see Figs. 12-13) embodiments, taking into account the location of each of fuel injection valve 70, collector mounting bracket 36 is detachably connected to collector 38B. In lieu thereof, collector mounting
10 bracket 36 may be integrally formed with collector 38B, such that the collector part can be directly connected to the intake-port side wall of cylinder head 30. This eliminates the necessity of the collector mounting bracket.

15 The construction and operation of the intake system of the fourth embodiment are hereunder described in detail in reference to Figs. 14A-14C. The fundamental construction of the intake system of the fourth embodiment is similar to that of the first embodiment having the
20 two-split collector 38 composed of upper and lower collector portions 42 and 44 both made of a lightweight synthetic resin material. In addition to the above, in the intake system of the fourth embodiment, as a variable valve actuation system, only the previously-discussed
25 variable lift and working angle control mechanism 10 is used in the intake valve side, while only the variable phase control mechanism 20 is used in the exhaust valve side. In order to obtain the operation and effects as discussed later, in the system of the fourth embodiment
30 the phase of central angle ϕ of the working angle of intake valve 1 is set to a phase retarded by approximately 100 degrees with respect to TDC on the exhaust stroke. For the purpose of enhanced engine power output, the working

angle of the exhaust valve is set to a comparatively large working angle (corresponding to a time period of the exhaust stroke) exceeding 180 degrees.

As shown in Fig. 14A, during idling after starting,
5 a relatively small quantity of intake-air is required, and thus the intake valve closure timing IVC is advanced with respect to BDC. In order to enhance the combustion stability during idling, the exhaust valve closure timing EVC is set to a timing point closer to TDC, and additionally
10 the intake valve open timing IVO is greatly retarded with respect to TDC. That is, intake valve open timing IVO is preprogrammed or set so that intake valve 1 is opened when the vacuum (negative pressure) in the engine cylinder becomes high, thus increasing the flow velocity of intake
15 air and promoting atomization of fuel injected. To attain the IVO, IVC, and EVC suitable for idling, the working angle EA of intake valve 1 is adjusted to a smaller working angle by means of variable lift and working angle control mechanism 10 installed on the intake valve side, than
20 that of each of the middle load condition (see Fig. 14B) and the high load condition (see Fig. 14C). On the other and, during idling the phase of central angle ϕ of the working angle of intake valve 1 is advanced by means of variable phase control mechanism 20 installed on the
25 exhaust valve side, in comparison with the middle load condition.

During high load condition containing high load condition (see Fig. 14C), to increase the intake-air quantity, intake valve closure timing IVC is retarded
30 to a timing point after BDC. At high load operation, the combusting state is good and the combustion stability is comparatively high, and therefore intake valve open timing IVO is set to a timing point nearby TDC, thus reducing

the pumping loss. To attain the IVC and IVO suitable for high load condition, the working angle EA of intake valve 1 is adjusted to a larger working angle than a working angle suitable for idling.

5 During middle load condition or in middle load range (see Fig. 14B), it is desirable to enhance fuel economy by increasing internal EGR (exhaust gas or combustion gas recirculated from the exhaust port through the engine cylinder back to the intake port side) and thus reducing
10 the pumping loss. Suppose that the conventional throttle valve control is used to allow a more complete utilization of internal EGR. In this case, the vacuum is created downstream of the throttle by way of the reduced throttle valve opening, and a valve overlap period during which
15 both the intake and exhaust valves are open together before and after TDC on the exhaust stroke is provided. As a result of this, near TDC on the exhaust stroke, combustion gas is recirculated from the exhaust port through the engine cylinder back to the intake port side in which
20 the vacuum is created, in accordance with the upstroke of the reciprocating piston. The combustion gas (internal EGR) recirculated back to the intake port side is sucked into the engine cylinder together with fresh air, after the exhaust valve has been closed on the
25 downstroke of the piston, that is, on the intake stroke. If such a valve overlap is used during middle load condition in the intake system of the fourth embodiment, there are some drawbacks. In the system of the fourth embodiment, collector 38 is made of a synthetic resin material for
30 a more compact installation and a simplicity in design and air cleaner 46 is built in collector 38. Firstly, if high-temperature combustion gas is recirculated back to the intake port side due to the valve overlap, there

is an increased tendency for damage to synthetic resin parts such as collector 38 to occur and for degradation in air cleaner 46 to be promoted. Secondly, in the system of the fourth embodiment that the intake-air quantity
5 is mainly adjusted by way of IVO control and IVC control, even during the middle load operation, the pressure in collector 38 becomes a pressure value closer to an atmospheric pressure or a slight vacuum pressure adjusted by vacuum control valve 64. Thus, even when the intake
10 valve and the exhaust valve both open before TDC, there is a very small quantity of combustion gas (internal EGR) recirculated from the exhaust port through the engine cylinder back to the intake port side. For the reasons set forth above, it is difficult to produce a desired
15 quantity of internal EGR. Therefore, in the system of the fourth embodiment, in order to produce the desired internal EGR without providing the valve overlap period during middle load operation (see Fig. 14B), exhaust valve closure timing EVC is retarded to a timing point after
20 TDC, while intake valve open timing IVO is set or retarded to a timing point after EVC. As a result of this, during the exhaust stroke with the upstroke of the piston, the exhaust valve remains open, while the intake valve remains closed. Just after TDC on the exhaust stroke, the exhaust
25 valve remains open. Therefore, the combustion gas once discharged into the exhaust port, is introduced again into the cylinder. During this time period, the intake valve remains closed, and thus there is no risk of counter-flow of combustion gas to the intake port side
30 to occur. At a timing when an amount of the internal EGR (residual gas) approaches to a desired value, the system of the fourth embodiment operates to close the exhaust valve so as to prevent the combustion gas from being

introduced from the exhaust port into the cylinder and thereafter to open the intake valve so as to suck fresh air into the cylinder. Thus, it is possible to allow a more complete utilization of internal EGR without

5 high-temperature burnt gas flowing back to the intake port side. In addition to the above, in the system of the fourth embodiment, as can be seen from the valve timing characteristics of Figs. 14A, 14B, and 14C, the working angle of the exhaust valve is set to be greater than 180

10 degrees. As can be appreciated from a phase retard from the EVC point (near TDC) of Fig. 14A to the EVC point (after TDC) and a change in EVO from the EVO point (before BDC) of Fig. 14A to the EVO point (near BDC) of Fig. 14B, exhaust valve open timing EVO tends to approaches to BDC,

15 as exhaust valve closure timing EVC is retarded with respect to TDC. This is advantageous with respect to enhancement in the expansion ratio and thermal efficiency (consequently, improved fuel economy).

During middle load operation, it is necessary to

20 enlarge the working angle EA of intake valve 1, since the intake-air quantity required for the middle load operation is larger than that of the idling operation. In the system of the fourth embodiment, during the middle load condition (see Fig. 14B), the working angle EA of

25 intake valve 1 is set to as large a working angle as possible within a period of time after exhaust valve closure timing EVC. As a result of this, exhaust valve closure timing EVC is substantially identical to intake valve open timing IVO. In other words, intake valve open timing IVO is set

30 to a timing point just after the EVC point.

In the shown embodiment, the collector having a major part of the entire intake-air length extending from the inlet-valve port to the intake-air inlet is made of a

synthetic resin material and the air cleaner is built in the collector. In case that there is a less heat damage to the collector and air cleaner, that is, a part of the intake-air passage is not made of synthetic resin and the air cleaner is located outside of the collector, it is possible to allow flow of some combustion gas back to the intake port side. In this case, it is unnecessary to set the EVC point always to a timing point after TDC, and therefore it is possible to ensure a desired quantity of internal EGR by setting of a minus valve overlap that the IVO point is later than the EVC point.

As described previously, in the system of the fourth embodiment related to Figs. 14A-14C, only the previously-discussed variable lift and working angle control mechanism 10 is used in the intake valve side, while only the variable phase control mechanism 20 is used in the exhaust valve side. In lieu thereof, variable phase control mechanism 20 as well as variable lift and working angle control mechanism 10 may be used in the intake valve side, whereas only the variable phase control mechanism 20 may be used in the exhaust valve side. In this case, the construction of the variable valve actuation system is somewhat complicated, however, it is possible to intake valve open timing IVO independently of intake valve closure timing IVC, in such a manner as to adjust the charging efficiency toward a maximum efficiency in accordance with a rise in engine speed, while adjusting the IVO point in the same manner as the system of the fourth embodiment. Thus, it is possible to enhance engine power output within the entire engine operating range.

The construction and operation of the intake system of the fifth embodiment are hereunder described in detail

in reference to Figs. 15A-15C. The fundamental construction of the intake system of the fifth embodiment is similar to that of the first embodiment having the two-slit collector 38 composed of upper and lower collector portions both made of a lightweight synthetic resin material. In the same manner as the fourth embodiment related to Figs. 14A-14C, in the intake system of the fifth embodiment related to Figs. 15A-15C, as a variable valve actuation system, only the variable lift and working angle control mechanism 10 is used in the intake valve side, while only the variable phase control mechanism 20 is used in the exhaust valve side. Similarly to the fourth embodiment, in the intake system of the fifth embodiment, the phase of central angle ϕ of the working angle of intake valve 1 is set to a phase retarded by approximately 100 degrees with respect to TDC on the exhaust stroke. On the other hand, the working angle of the exhaust valve used in the system of the fifth embodiment is set to a comparatively large working angle exceeding 180 degrees and smaller than that of the fourth embodiment, since exhaust valve closure timing EVC has to be advanced with respect to TDC during the middle load operation (see Fig. 15B).

Setting of both of the exhaust valve closure timing EVC and intake valve open timing IVO suitable for the idling condition (see Fig. 15A) and high load condition (see Fig. 15C) in the system of the fifth embodiment is similar to that of the fourth embodiment.

On the other hand, according to the system of the fifth embodiment, during the middle load condition (see Fig. 15B), exhaust valve closure timing EVC is advanced with respect to TDC, whereas intake valve open timing IVO is retarded with respect to TDC. Additionally, a time

period B from the TDC position to intake valve open timing IVO is set to be longer than a time period A from exhaust valve closure timing EVC to the TDC position, that is, $A < B$. Owing to the previously-discussed setting of EVC and IVO performed by the system of the fifth embodiment during the middle load condition (see Fig. 15B), combustion gas can be certainly sealed inside the cylinder, since the intake valve is not yet opened when the exhaust valve is closed during the last phase of the exhaust stroke with the upstroke of the reciprocating piston. That is, it is possible to adjust the amount of internal EGR or the amount of residual gas depending on exhaust valve closure timing EVC. The residual gas sealed inside the cylinder can be compressed during the time period A from exhaust valve closure timing EVC to the TDC position. Thereafter, the system of the fifth embodiment adjusts intake valve closure timing IVC such that intake valve 1 remains closed even at the early part of the intake stroke with the downstroke of the piston after TDC. As a result of this, the residual gas in the cylinder expands, thus resulting in a reduction in in-cylinder pressure. When the time period B (greater than A) from the TDC position to intake valve open timing IVO expires, the in-cylinder pressure remarkably reduces to produce a vacuum pressure in the cylinder. Thereafter, the intake valve is opened. That is, the intake valve is opened at the timing when the residual gas sealed inside the cylinder re-expands and the in-cylinder pressure becomes less than the pressure of the intake port side, so as to effectively introduce fresh air into the cylinder with the intake valve timely opened. Therefore, there is no risk of counter-flow of the residual gas toward the intake port side, thus ensuring a sufficient amount of residual gas

(internal EGR). Additionally, in the system of the fifth embodiment, during the middle load condition combustion gas is sealed inside the cylinder by phase-advancing exhaust valve closure timing EVC with respect to TDC.

5 Therefore, for the same quantity of internal EGR, the use of EVC phase-advanced from TDC is superior to the use of valve overlap in a reduction in a pumping loss occurring when the exhaust gas passes through the outlet-valve port, that is, in improved fuel economy.

10 However, in case of the system of the fifth embodiment, exhaust valve open timing EVO and exhaust valve closure timing EVC are simultaneously adjusted by means of only variable phase control system 20, and additionally the working angle of the exhaust valve side is fixed to a
15 predetermined working angle above 180 degrees, taking into account the maximum engine power output. In such a case, if exhaust valve closure timing EVC is advanced with respect to TDC in order to increase a quantity of internal EGR during the middle load condition, exhaust
20 valve open timing EVO is inevitably greatly phase-advanced toward BDC, because of the fixed working angle of the exhaust valve. This reduces the expansion ratio and increases fuel consumption. That is, it is difficult to reconcile or balance two contradictory requirements, that
25 is, increased engine power output and reduced fuel consumption at middle load operation. To balance these contradictory requirements, the intake system of the sixth embodiment is proposed.

30 The construction and operation of the intake system of the sixth embodiment are hereunder described in detail in reference to Figs. 16A-16C. The fundamental construction of the intake system of the fifth embodiment is similar to that of the first embodiment having the

two-slit collector 38 composed of upper and lower collector portions both made of a lightweight synthetic resin material. In the system of the sixth embodiment, as a variable valve actuation system, only the variable lift and working angle control mechanism 10 is used in the intake valve side. Note that variable lift and working angle control mechanism 10 as well as variable phase control mechanism 20 is used in the exhaust valve side. The system of the sixth embodiment related to Figs. 16A-16C has variable lift and working angle control mechanism 10 as well as variable phase control mechanism 20 in the exhaust valve side, thereby being more complicated in construction in comparison with the fifth embodiment related to Figs. 15A-15C. On the other hand, it is possible to variably adjust exhaust valve open timing EVO and exhaust valve closure timing EVC independently of each other by virtue of variable lift and working angle control mechanism 10 in addition to variable phase control mechanism 20 in the exhaust valve side. Therefore, in the system of the sixth embodiment, exhaust valve closure timing EVC suitable for each of idling, middle and high load operations and exhaust valve open timing EVO suitable for high load operation are adjusted in the same manner as that described for the system of the fifth embodiment related to Figs. 15A-15C. On the other hand, according to the system of the sixth embodiment, it is possible to set or adjust exhaust valve open timing EVO in close vicinity to BDC, thereby reconciling two contradictory requirements, namely increased engine power output and reduced fuel consumption.

The entire contents of Japanese Patent Application Nos. P2001-77467 (filed March 19, 2001), P2001-69870

(filed March 12, 2001), and P2001-83960 (filed March 23, 2001) are incorporated herein by reference.

While the foregoing is a description of the preferred embodiments carried out the invention, it will be understood that the invention is not limited to the particular embodiments shown and described herein, but that various changes and modifications may be made without departing from the scope or spirit of this invention as defined by the following claims.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209